

PULITENE



DESCRIPTION:

Spray detergent for the cleaning of Polyethylene (PE) and Polypropylene (PP) to be welded.

INSTRUCTIONS FOR USE:

Thanks to its very efficient delivery valve it is sufficient to spray a little quantity of product on the part to be welded. Wait the product has evaporated then weld as usual.

TECHNICAL DATA:

Appearance	colorless liquid
Odor	characteristic alcohol
Relative density of the liquid phase	$0,786 \pm 0,05 \text{ g/cm}^3$
Relative density of the mixture	$0,715 \pm 0,05 \text{ g/cm}^3$
Flash point liquid phase	$< 14 \text{ }^\circ\text{C}$
Propellant flammability	extremely flammable
Auto-flammability	$\sim 360 \text{ }^\circ\text{C}$
Flammability limits propellant	$1.8 \div 9.5 \%$
Water solubility	partial
Lipo-solubility	total
Container volume	520 ml
Product volume	400 ml
Pressure of the container	12 bar
Burst pressure of the container	15 bar

PACKAGING:

Bombs spray 400 ml, boxes of 12 pcs.

INGREDIENTS:

Isopropyl Alcohol, Petroleum Distillates.

Last update: 19.04.2023



PRODOTTI CHIMICI E TECNICI - CHEMICAL AND TECHNICAL PRODUCTS

FACOT CHEMICALS Srl - Via Crema 44, 26010 Capralba CR, Italy - Tel. +39 0373450642 - info@facot.it - www.facotchemicals.com



CHEMISTRY IN ACTION