

# PULITENE DETERGENTE



## DESCRIPTION:

Special solvent in a bottle for the cleaning of polyethylene, polypropylene and PVC to be welded.

## INSTRUCTIONS FOR USE:

Pour a little quantity of product on a cloth and wipe the piece to be welded in order to eliminate any possible impurity that may affect the welding. Wait a few seconds the product has evaporated than weld as usual.

## TECHNICAL DATA:

Appearance	colorless liquid
Smell	characteristic
pH at @ 20 °C	not applicable
Boiling point	~ 75 °C
Flash point	-4 °C
Fusion point	-84 °C
Relative density	0,900 ± 0,050 g/cm <sup>3</sup>
Solubility in water	partially soluble (~ 8 %)
Lipid solubility	complete
Auto-ignition temperature	425 °C
Vapour pressure at @ 20 °C	~ 101 hPa
VOC	100%

## PACKAGING:

Bottle 750 ml with sprayer, boxes with 6 pieces.

## INGREDIENTS:

Ethyl Acetate.

Last update: 19.04.2023



PRODOTTI CHIMICI E TECNICI - CHEMICAL AND TECHNICAL PRODUCTS

FACOT CHEMICALS Srl - Via Crema 44, 26010 Capralba CR, Italy - Tel. +39 0373450642 - [info@facot.it](mailto:info@facot.it) - [www.facotchemicals.com](http://www.facotchemicals.com)



CHEMISTRY IN ACTION