

SBLOKKA



DESCRIPTION:

Releasing agent, water-repellent, lubricating, water-repellent, antioxidant.

CHARACTERISTICS:

It immediately releases screws, bolts, threads, metal couplings blocked by oxides, rust, scales, paints or rubber. It prevents treated surfaces from oxidation and corrosion. It has a lubricating action and can be used on threads. Useful to expel humidity also from electric systems. Provided with a universal valve, SBLOKKA can be also sprayed handling the bomb upside-down.

INSTRUCTIONS FOR USE:

Spray a great quantity of it on the encrusted surface. Wait for a few minutes to allow a total penetration. Then loosen the piece.

WARNINGS:

It contains chlorinated solvents. Toxic when inhaled or ingested. Keep out of children's reach. Aerosol bomb under pressure. Protect from sun-rays and do not expose to a temperature higher than 50 °C. Do not burn even after using it. Do not spray on flames or on incandescent bodies. Avoid direct inhalation or eye contact.

CHEMICAL AND PHYSICAL PROPERTIES:

Physical state	Container under pressure with base and liquefied gas
Odour	Peculiar of solvents
Colour	Colourless
Specific weight @ 20 °C	0,797 g/cm ³
Aerosol bomb volume	520 ml
Aerosol product volume	400 ml
Pressure @ 20 °C	2,8 Bars
Aerosol product flash point	Lower than 21 °C
Propellant flash point	Lower than 0 °C
pH	Unmeasurable
Water solubility	Insoluble
Oil solubility	Soluble
Foaming power	Not foaming

Last update: 19.04.2023



PRODOTTI CHIMICI E TECNICI - CHEMICAL AND TECHNICAL PRODUCTS

FACOT CHEMICALS Srl - Via Crema 44, 26010 Capralba CR, Italy - Tel. +39 0373450642 - info@facot.it - www.facotchemicals.com



CHEMISTRY IN ACTION